



CUDA-GDB CUDA DEBUGGER

DU-05227-042 _v5.5 | May 2013

User Manual



TABLE OF CONTENTS

Chapter 1. Introduction.....	1
1.1 What is CUDA-GDB?	1
1.2 Supported Features	1
1.3 About This Document	2
Chapter 2. Release Notes.....	3
Chapter 3. Getting Started.....	6
3.1 Installation Instructions	6
3.2 Setting Up the Debugger Environment	6
3.2.1 Linux	6
3.2.2 Mac OS X	6
3.2.3 Temporary Directory	7
3.3 Compiling the Application	7
3.3.1 Debug Compilation	7
3.3.2 Compiling For Specific GPU architectures	8
3.4 Using the Debugger	8
3.4.1 Single-GPU Debugging	9
3.4.2 Single-GPU Debugging with the Desktop Manager Running	9
3.4.3 Multi-GPU Debugging	9
3.4.4 Multi-GPU Debugging in Console Mode	10
3.4.5 Multi-GPU Debugging with the Desktop Manager Running	10
3.4.6 Remote Debugging	11
3.4.7 Multiple Debuggers	11
3.4.8 Attaching/Detaching	11
3.4.9 CUDA/OpenGL Interop Applications on Linux	11
Chapter 4. CUDA-GDB Extensions.....	13
4.1 Command Naming Convention	13
4.2 Getting Help	13
4.3 Initialization File	13
4.4 GUI Integration	14
Chapter 5. Kernel Focus.....	15
5.1 Software Coordinates vs. Hardware Coordinates	15
5.2 Current Focus	15
5.3 Switching Focus	16
Chapter 6. Program Execution.....	17
6.1 Interrupting the Application	17
6.2 Single Stepping	17
Chapter 7. Breakpoints.....	19
7.1 Symbolic Breakpoints	19
7.2 Line Breakpoints	20
7.3 Address Breakpoints	20

7.4 Kernel Entry Breakpoints	20
7.5 Conditional Breakpoints	20
Chapter 8. Inspecting Program State.....	22
8.1 Memory and Variables	22
8.2 Variable Storage and Accessibility	22
8.3 Inspecting Textures	23
8.4 Info CUDA Commands	23
8.4.1 info cuda devices	24
8.4.2 info cuda sms	24
8.4.3 info cuda warps	25
8.4.4 info cuda lanes	25
8.4.5 info cuda kernels	25
8.4.6 info cuda blocks	26
8.4.7 info cuda threads	26
8.4.8 info cuda launch trace	27
8.4.9 info cuda launch children	28
8.4.10 info cuda contexts	28
8.5 Disassembly	28
Chapter 9. Context and Kernel Events.....	29
9.1 Display CUDA context events	29
9.2 Display CUDA kernel events	29
9.3 Examples of displayed events	30
Chapter 10. Checking Memory Errors.....	31
10.1 Increasing the Precision of Memory Errors With Autostep	31
10.1.1 Usage	32
10.1.2 Related Commands	33
10.1.2.1 info autosteps	33
10.1.2.2 disable autosteps n	33
10.1.2.3 delete autosteps n	33
10.1.2.4 ignore n i	33
10.2 GPU Error Reporting	33
Chapter 11. Checking API Errors.....	36
Chapter 12. Walk-Through Examples.....	37
12.1 Example 1: bitreverse	37
12.1.1 Walking through the Code	38
12.2 Example 2: autostep	40
12.2.1 Debugging with Autosteps	41
12.3 Example 3: Debugging an MPI CUDA Application	42
Appendix A. Supported Platforms.....	44
A.1 Host Platform Requirements	44
Appendix B. Known Issues.....	46

LIST OF TABLES

Table 1	CUDA Exception Codes.....	33
---------	---------------------------	----

Chapter 1.

INTRODUCTION

This document introduces CUDA-GDB, the NVIDIA® CUDA™ debugger for Linux and Mac OS.

1.1 What is CUDA-GDB?

CUDA-GDB is the NVIDIA tool for debugging CUDA applications running on Linux and Mac. CUDA-GDB is an extension to the x86-64 port of GDB, the GNU Project debugger. The tool provides developers with a mechanism for debugging CUDA applications running on actual hardware. This enables developers to debug applications without the potential variations introduced by simulation and emulation environments.

CUDA-GDB runs on Linux and Mac OS X, 32-bit and 64-bit. CUDA-GDB is based on GDB 7.2 on both Linux and Mac OS X.

1.2 Supported Features

CUDA-GDB is designed to present the user with a seamless debugging environment that allows simultaneous debugging of both GPU and CPU code within the same application. Just as programming in CUDA C is an extension to C programming, debugging with CUDA-GDB is a natural extension to debugging with GDB. The existing GDB debugging features are inherently present for debugging the host code, and additional features have been provided to support debugging CUDA device code.

CUDA-GDB supports C and C++ CUDA applications. All the C++ features supported by the NVCC compiler can be debugged by CUDA-GDB.

CUDA-GDB allows the user to set breakpoints, to single-step CUDA applications, and also to inspect and modify the memory and variables of any given thread running on the hardware.

CUDA-GDB supports debugging all CUDA applications, whether they use the CUDA driver API, the CUDA runtime API, or both.

CUDA-GDB supports debugging kernels that have been compiled for specific CUDA architectures, such as **sm_10** or **sm_20**, but also supports debugging kernels compiled at runtime, referred to as just-in-time compilation, or JIT compilation for short.

1.3 About This Document

This document is the main documentation for CUDA-GDB and is organized more as a user manual than a reference manual. The rest of the document will describe how to install and use CUDA-GDB to debug CUDA kernels and how to use the new CUDA commands that have been added to GDB. Some walk-through examples are also provided. It is assumed that the user already knows the basic GDB commands used to debug host applications.

Chapter 2.

RELEASE NOTES

5.5 Release

Kernel Launch Stack

Two new commands, `info cuda launch stack` and `info cuda launch children`, are introduced to display the kernel launch stack and the children kernel of a given kernel when Dynamic Parallelism is used.

Single-GPU Debugging (BETA)

CUDA-GDB can now be used to debug a CUDA application on the same GPU that is rendering the desktop GUI. This feature also enables debugging of long-running or indefinite CUDA kernels that would otherwise encounter a launch timeout. In addition, multiple CUDA-GDB sessions can simultaneously debug CUDA applications on the same GPU. This feature is available on Linux with SM3.5 devices, and can be enabled using the `set cuda software_preemption on` command prior to running an application.

5.0 Release

Dynamic Parallelism Support

CUDA-GDB fully supports Dynamic Parallelism, a new feature introduced with the 5.0 toolkit. The debugger is able to track the kernels launched from another kernel and to inspect and modify variables like any other CPU-launched kernel.

Attach/Detach

It is now possible to attach to a CUDA application that is already running. It is also possible to detach from the application before letting it run to completion. When attached, all the usual features of the debugger are available to the user, as if the application had been launched from the debugger. This feature is also supported with applications using Dynamic Parallelism.

Attach on exception

Using the environment variable `CUDA_DEVICE_WAITS_ON_EXCEPTION`, the application will run normally until a device exception occurs. Then the application will wait for the debugger to attach itself to it for further debugging.

API Error Reporting

Checking the error code of all the CUDA driver API and CUDA runtime API function calls is vital to ensure the correctness of a CUDA application. Now the debugger is able to report, and even stop, when any API call returns an error. See `set cuda api_failures` for more information.

Inlined Subroutine Support

Inlined subroutines are now accessible from the debugger on SM 2.0 and above. The user can inspect the local variables of those subroutines and visit the call frame stack as if the routines were not inlined.

4.2 Release

Kepler Support

The primary change in Release 4.2 of CUDA-GDB is the addition of support for the new Kepler architecture. There are no other user-visible changes in this release.

4.1 Release

Source Base Upgraded to GDB 7.2

Until now, CUDA-GDB was based on GDB 6.6 on Linux, and GDB 6.3.5 on Darwin (the Apple branch). Now, both versions of CUDA-GDB are using the same 7.2 source base.

Now CUDA-GDB supports newer versions of GCC (tested up to GCC 4.5), has better support for DWARF3 debug information, and better C++ debugging support.

Simultaneous Sessions Support

With the 4.1 release, the single CUDA-GDB process restriction is lifted. Now, multiple CUDA-GDB sessions are allowed to co-exist as long as the GPUs are not shared between the applications being processed. For instance, one CUDA-GDB process can debug process foo using GPU 0 while another CUDA-GDB process debugs process bar using GPU 1. The exclusive of GPUs can be enforced with the `CUDA_VISIBLE_DEVICES` environment variable.

New Autostep Command

A new 'autostep' command was added. The command increases the precision of CUDA exceptions by automatically single-stepping through portions of code.

Under normal execution, the thread and instruction where an exception occurred may be imprecisely reported. However, the exact instruction that generates the

exception can be determined if the program is being single-stepped when the exception occurs.

Manually single-stepping through a program is a slow and tedious process. Therefore 'autostep' aides the user by allowing them to specify sections of code where they suspect an exception could occur. These sections are automatically single-stepped through when the program is running, and any exception that occurs within these sections is precisely reported.

Type 'help autostep' from CUDA-GDB for the syntax and usage of the command.

Multiple Context Support

On GPUs with compute capability of SM20 or higher, debugging multiple contexts on the same GPU is now supported. It was a known limitation until now.

Device Assertions Support

The R285 driver released with the 4.1 version of the toolkit supports device assertions. CUDA_GDB supports the assertion call and stops the execution of the application when the assertion is hit. Then the variables and memory can be inspected as usual. The application can also be resumed past the assertion if needed. Use the 'set cuda hide_internal_frames' option to expose/hide the system call frames (hidden by default).

Temporary Directory

By default, the debugger API will use /tmp as the directory to store temporary files. To select a different directory, the \$TMPDIR environment variable and the API CUDBG_APICLIENT_PID variable must be set.

Chapter 3.

GETTING STARTED

Included in this chapter are instructions for installing CUDA-GDB and for using NVCC, the NVIDIA CUDA compiler driver, to compile CUDA programs for debugging.

3.1 Installation Instructions

Follow these steps to install CUDA-GDB.

1. Visit the NVIDIA CUDA Zone download page:
http://www.nvidia.com/object/cuda_get.html
2. Select the appropriate operating system—MacOS X or Linux.
(See [Host Platform Requirements](#).)
3. Download and install the CUDA Driver.
4. Download and install the CUDA Toolkit.

3.2 Setting Up the Debugger Environment

3.2.1 Linux

Set up the `PATH` and `LD_LIBRARY_PATH` environment variables:

```
export PATH=/usr/local/cuda-5.5/bin:$PATH
export LD_LIBRARY_PATH=/usr/local/cuda-5.5/lib64:/usr/local/cuda-5.5/
lib:$LD_LIBRARY_PATH
```

3.2.2 Mac OS X

Set up the `PATH` and `DYLD_LIBRARY_PATH` environment variables:

```
export PATH=/Developer/NVIDIA/CUDA-5.5/bin:$PATH
export DYLD_LIBRARY_PATH=/Developer/NVIDIA/CUDA-5.5/lib:$DYLD_LIBRARY_PATH
```

Also, if you are unable to execute CUDA-GDB or if you hit the **Unable to find Mach task port for processid** error, try resetting the correct permissions with the following commands:

```
sudo chgrp procmod /Developer/NVIDIA/CUDA-5.5/bin/cuda-binary-gdb
sudo chmod 2755 /Developer/NVIDIA/CUDA-5.5/bin/cuda-binary-gdb
sudo chmod 755 /Developer/NVIDIA/CUDA-5.5/bin/cuda-gdb
```

You must also make sure that the **taskgated** daemon allows the processes in the **procmod** group to access Task Ports. That option is turned on by default by launching the **taskgated** with the **-p** option. To make it a permanent option, edit **/System/Library/LaunchDaemons/com.apple.taskgated.plist**. See **man taskgated** for more information. Here is an example:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple Inc.//DTD PLIST 1.0//EN" "http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
<dict>
  <key>Label</key>
  <string>com.apple.taskgated</string>
  <key>MachServices</key>
  <dict>
    <key>com.apple.taskgated</key>
    <dict>
      <key>TaskSpecialPort</key>
      <integer>9</integer>
    </dict>
  </dict>
  <key>ProgramArguments</key>
  <array>
    <string>/usr/libexec/taskgated</string>
    <string>-p</string>
    <string>-s</string>
  </array>
</dict>
</plist>
```

After editing the file, the system must be rebooted or the daemon stopped and relaunched for the change to take effect.



As every application in the **procmod** group will have higher privileges, adding the **-p** option to the **taskgated** daemon is a possible security risk.

3.2.3 Temporary Directory

By default, CUDA-GDB uses **/tmp** as the directory to store temporary files. To select a different directory, set the **\$TMPDIR** environment variable.

3.3 Compiling the Application

3.3.1 Debug Compilation

NVCC, the NVIDIA CUDA compiler driver, provides a mechanism for generating the debugging information necessary for CUDA-GDB to work properly. The **-g -G** option

pair must be passed to NVCC when an application is compiled in order to debug with CUDA-GDB; for example,

```
nvcc -g -G foo.cu -o foo
```

Using this line to compile the CUDA application `foo.cu`

- ▶ forces `-O0` compilation, with the exception of very limited dead-code eliminations and register-spilling optimizations.
- ▶ makes the compiler include debug information in the executable

3.3.2 Compiling For Specific GPU architectures

By default, the compiler will only generate PTX code for the `compute_10` virtual architecture. Then, at runtime, the kernels are recompiled for the GPU architecture of the target GPU(s). Compiling for a specific virtual architecture guarantees that the application will work for any GPU architecture after that, for a trade-off in performance. This is done for forward-compatibility.

It is highly recommended to compile the application once and for all for the GPU architectures targeted by the application, and to generate the PTX code for the latest virtual architecture for forward compatibility.

A GPU architecture is defined by its compute capability. The list of GPUs and their respective compute capability, see <https://developer.nvidia.com/cuda-gpus>. The same application can be compiled for multiple GPU architectures. Use the `-gencode` compilation option to dictate which GPU architecture to compile for. The option can be specified multiple times.

For instance, to compile an application for a GPU with compute capability 3.0, add the following flag to the compilation command:

```
-gencode arch=compute_30,code=sm_30
```

To compile PTX code for any future architecture past the compute capability 3.5, add the following flag to the compilation command:

```
-gencode arch=compute_35,code=compute_35
```

For additional information, please consult the compiler documentation at <http://docs.nvidia.com/cuda/cuda-compiler-driver-nvcc/index.html#extended-notation>

3.4 Using the Debugger

Debugging a CUDA GPU involves pausing that GPU. When the graphics desktop manager is running on the same GPU, then debugging that GPU freezes the GUI and makes the desktop unusable. To avoid this, use CUDA-GDB in the following system configurations:

3.4.1 Single-GPU Debugging

In a single GPU system, CUDA-GDB can be used to debug CUDA applications only if no X11 server (on Linux) or no Aqua desktop manager (on Mac OS X) is running on that system. On Linux you can stop the X11 server by stopping the **gdm** service. On Mac OS X you can log in with **>console** as the user name in the desktop UI login screen. This allows CUDA applications to be executed and debugged in a single GPU configuration.

3.4.2 Single-GPU Debugging with the Desktop Manager Running

CUDA-GDB can be used to debug CUDA applications on the same GPU that is running the desktop GUI.



This is a BETA feature available on Linux and supports devices with SM3.5 compute capability.

There are two ways to enable this functionality:

- ▶ Use the following command:

```
set cuda software_preemption on
```

- ▶ Export the following environment variable:

```
CUDA_DEBUGGER_SOFTWARE_PREEMPTION=1
```

Either of the options above will activate software preemption. These options must be set **prior** to running the application. When the GPU hits a breakpoint or any other event that would normally cause the GPU to freeze, CUDA-GDB releases the GPU for use by the desktop or other applications. This enables CUDA-GDB to debug a CUDA application on the same GPU that is running the desktop GUI, and also enables simultaneous debugging of multiple CUDA applications on the same GPU.



The options listed above are ignored for GPUs with less than SM3.5 compute capability.

3.4.3 Multi-GPU Debugging

Multi-GPU debugging is not much different than single-GPU debugging except for a few additional CUDA-GDB commands that let you switch between the GPUs.

Any GPU hitting a breakpoint will pause all the GPUs running CUDA on that system. Once paused, you can use **info cuda kernels** to view all the active kernels and the GPUs they are running on. When any GPU is resumed, all the GPUs are resumed.



If the `CUDA_VISIBLE_DEVICES` environment is used, only the specified devices are suspended and resumed.

All CUDA-capable GPUs may run one or more kernels. To switch to an active kernel, use `cuda kernel <n>`, where `n` is the ID of the kernel retrieved from `info cuda kernels`.



The same kernel can be loaded and used by different contexts and devices at the same time. When a breakpoint is set in such a kernel, by either name or file name and line number, it will be resolved arbitrarily to only one instance of that kernel. With the runtime API, the exact instance to which the breakpoint will be resolved cannot be controlled. With the driver API, the user can control the instance to which the breakpoint will be resolved to by setting the breakpoint *right after* its module is loaded.

3.4.4 Multi-GPU Debugging in Console Mode

CUDA-GDB allows simultaneous debugging of applications running CUDA kernels on multiple GPUs. In console mode, CUDA-GDB can be used to pause and debug every GPU in the system. You can enable console mode as described above for the single GPU console mode.

3.4.5 Multi-GPU Debugging with the Desktop Manager Running

This can be achieved by running the desktop GUI on one GPU and CUDA on the other GPU to avoid hanging the desktop GUI.

On Linux

The CUDA driver automatically excludes the GPU used by X11 from being visible to the application being debugged. This might alter the behavior of the application since, if there are n GPUs in the system, then only $n-1$ GPUs will be visible to the application.

On Mac OS X

The CUDA driver exposes every CUDA-capable GPU in the system, including the one used by the Aqua desktop manager. To determine which GPU should be used for CUDA, run the `1_Uilities/deviceQuery` CUDA sample. A truncated example output of `deviceQuery` is shown below.

```
Detected 2 CUDA Capable device(s)

Device 0: "GeForce GT 330M"
  CUDA Driver Version / Runtime Version      5.5 / 5.5
  CUDA Capability Major/Minor version number: 1.2
  Total amount of global memory:              512 MBytes (536543232 bytes)
  ( 6) Multiprocessors x ( 8) CUDA Cores/MP: 48 CUDA Cores
  [... truncated output ...]
```

```
Device 1: "Quadro K5000"
  CUDA Driver Version / Runtime Version      5.5 / 5.5
  CUDA Capability Major/Minor version number: 3.0
  Total amount of global memory:             4096 MBytes (4294508544 bytes)
  ( 8) Multiprocessors x (192) CUDA Cores/MP: 1536 CUDA Cores
  [... truncated output ...]

deviceQuery, CUDA Driver = CUDART, \
  CUDA Driver Version = 5.5, CUDA Runtime Version = 5.5, \
  NumDevs = 2, Device0 = GeForce GT 330M, Device1 = Quadro K5000
```

If Device 0 is rendering the desktop, then Device 1 must be selected for running and debugging the CUDA application. This exclusion of a device can be achieved by setting the **CUDA_VISIBLE_DEVICES** environment variable to the index of the device that will be used for CUDA. In this particular example, the value would be 1:

```
export CUDA_VISIBLE_DEVICES=1
```

3.4.6 Remote Debugging

To remotely debug an application, use SSH or VNC from the host system to connect to the target system. From there, CUDA-GDB can be launched in console mode.

3.4.7 Multiple Debuggers

In a multi-GPU environment, several debugging sessions may take place simultaneously as long as the CUDA devices are used exclusively. For instance, one instance of CUDA-GDB can debug a first application that uses the first GPU while another instance of CUDA-GDB debugs a second application that uses the second GPU. The exclusive use of a GPU is achieved by specifying which GPU is visible to the application by using the **CUDA_VISIBLE_DEVICES** environment variable.

```
CUDA_VISIBLE_DEVICES=1 cuda-gdb my_app
```

3.4.8 Attaching/Detaching

CUDA-GDB can attach to and detach from a CUDA application running on Fermi or Kepler GPUs, using GDB's built-in commands for attaching to or detaching from a process.

Additionally, if the environment variable **CUDA_DEVICE_WAITS_ON_EXCEPTION** is set to 1 prior to running the CUDA application, the application will run normally till a device exception occurs. The application will then wait for CUDA-GDB to attach itself to it for further debugging.

3.4.9 CUDA/OpenGL Interop Applications on Linux

Any CUDA application that uses OpenGL interoperability requires an active windows server. Such applications will fail to run under console mode debugging on both Linux and Mac OS X. However, if the X server is running on Linux, the render GPU will not be enumerated when debugging, so the application could still fail, unless the application uses the OpenGL device enumeration to access the render GPU. But if the X session

is running in non-interactive mode while using the debugger, the render GPU will be enumerated correctly.

1. Launch your X session in non-interactive mode.
 - a) Stop your X server.
 - b) Edit `/etc/X11/xorg.conf` to contain the following line in the Device section corresponding to your display:

```
Option "Interactive" "off"
```

- c) Restart your X server.
2. Log in remotely (SSH, etc.) and launch your application under CUDA-GDB.

This setup works properly for single-GPU and multi-GPU configurations.
3. Ensure your **DISPLAY** environment variable is set appropriately.

For example:

```
export DISPLAY=:0.0
```

While X is in non-interactive mode, interacting with the X session can cause your debugging session to stall or terminate.

Chapter 4.

CUDA-GDB EXTENSIONS

4.1 Command Naming Convention

The existing GDB commands are unchanged. Every new CUDA command or option is prefixed with the CUDA keyword. As much as possible, CUDA-GDB command names will be similar to the equivalent GDB commands used for debugging host code. For instance, the GDB command to display the host threads and switch to host thread 1 are, respectively:

```
(cuda-gdb) info threads
(cuda-gdb) thread 1
```

To display the CUDA threads and switch to cuda thread 1, the user only has to type:

```
(cuda-gdb) info cuda threads
(cuda-gdb) cuda thread 1
```

4.2 Getting Help

As with GDB commands, the built-in help for the CUDA commands is accessible from the **cuda-gdb** command line by using the help command:

```
(cuda-gdb) help cuda name_of_the_cuda_command
(cuda-gdb) help set cuda name_of_the_cuda_option
(cuda-gdb) help info cuda name_of_the_info_cuda_command
```

4.3 Initialization File

The initialization file for CUDA-GDB is named **.cuda-gdbinit** and follows the same rules as the standard **.gdbinit** file used by GDB. The initialization file may contain any CUDA- GDB command. Those commands will be processed in order when CUDA-GDB is launched.

4.4 GUI Integration

Emacs

CUDA-GDB works with GUD in Emacs and XEmacs. No extra step is required other than pointing to the right binary.

To use CUDA-GDB, the **`gud-gdb-command-name`** variable must be set to **`cuda-gdb`** **`annotate=3`**. Use **`M-x customize-variable`** to set the variable.

Ensure that **`cuda-gdb`** is present in the Emacs/XEmacs **`$PATH`**.

DDD

CUDA-GDB works with DDD. To use DDD with CUDA-GDB, launch DDD with the following command:

```
ddd --debugger cuda-gdb
```

`cuda-gdb` must be in your **`$PATH`**.

Chapter 5.

KERNEL FOCUS

A CUDA application may be running several host threads and many device threads. To simplify the visualization of information about the state of application, commands are applied to the entity in focus.

When the focus is set to a host thread, the commands will apply only to that host thread (unless the application is fully resumed, for instance). On the device side, the focus is always set to the lowest granularity level—the device thread.

5.1 Software Coordinates vs. Hardware Coordinates

A device thread belongs to a block, which in turn belongs to a kernel. Thread, block, and kernel are the software coordinates of the focus. A device thread runs on a lane. A lane belongs to a warp, which belongs to an SM, which in turn belongs to a device. Lane, warp, SM, and device are the hardware coordinates of the focus. Software and hardware coordinates can be used interchangeably and simultaneously as long as they remain coherent.

Another software coordinate is sometimes used: the grid. The difference between a grid and a kernel is the scope. The grid ID is unique per GPU whereas the kernel ID is unique across all GPUs. Therefore there is a 1:1 mapping between a kernel and a (grid,device) tuple.

Note: If software preemption is enabled (`set cuda software_preemption on`), hardware coordinates corresponding to a device thread are likely to change upon resuming execution on the device. However, software coordinates will remain intact and will not change for the lifetime of the device thread.

5.2 Current Focus

To inspect the current focus, use the `cuda` command followed by the coordinates of interest:

```
(cuda-gdb) cuda device sm warp lane block thread
block (0,0,0), thread (0,0,0), device 0, sm 0, warp 0, lane 0
(cuda-gdb) cuda kernel block thread
kernel 1, block (0,0,0), thread (0,0,0)
(cuda-gdb) cuda kernel
kernel 1
```

5.3 Switching Focus

To switch the current focus, use the `cuda` command followed by the coordinates to be changed:

```
(cuda-gdb) cuda device 0 sm 1 warp 2 lane 3
[Switching focus to CUDA kernel 1, grid 2, block (8,0,0), thread
(67,0,0), device 0, sm 1, warp 2, lane 3]
374 int totalThreads = gridDim.x * blockDim.x;
```

If the specified focus is not fully defined by the command, the debugger will assume that the omitted coordinates are set to the coordinates in the current focus, including the subcoordinates of the block and thread.

```
(cuda-gdb) cuda thread (15)
[Switching focus to CUDA kernel 1, grid 2, block (8,0,0), thread
(15,0,0), device 0, sm 1, warp 0, lane 15]
374 int totalThreads = gridDim.x * blockDim.x;
```

The parentheses for the block and thread arguments are optional.

```
(cuda-gdb) cuda block 1 thread 3
[Switching focus to CUDA kernel 1, grid 2, block (1,0,0), thread (3,0,0),
device 0, sm 3, warp 0, lane 3]
374 int totalThreads = gridDim.x * blockDim.x;
```

Chapter 6.

PROGRAM EXECUTION

Applications are launched the same way in CUDA-GDB as they are with GDB by using the run command. This chapter describes how to interrupt and single-step CUDA applications

6.1 Interrupting the Application

If the CUDA application appears to be hanging or stuck in an infinite loop, it is possible to manually interrupt the application by pressing **CTRL+C**. When the signal is received, the GPUs are suspended and the **cuda-gdb** prompt will appear.

At that point, the program can be inspected, modified, single-stepped, resumed, or terminated at the user's discretion.

This feature is limited to applications running within the debugger. It is not possible to break into and debug applications that have been launched outside the debugger.

6.2 Single Stepping

Single-stepping device code is supported. However, unlike host code single-stepping, device code single-stepping works at the warp level. This means that single-stepping a device kernel advances all the active threads in the warp currently in focus. The divergent threads in the warp are not single-stepped.

In order to advance the execution of more than one warp, a breakpoint must be set at the desired location and then the application must be fully resumed.

A special case is single-stepping over a thread barrier call: **__syncthreads()**. In this case, an implicit temporary breakpoint is set immediately after the barrier and all threads are resumed until the temporary breakpoint is hit.

On GPUs with **sm_type** lower than **sm_20** it is not possible to step over a subroutine in the device code. Instead, CUDA-GDB always steps into the device function. On GPUs with **sm_type sm_20** and higher, you can step in, over, or out of the device functions as long as they are not inlined. To force a function to not be inlined by the compiler, the **__noinline__** keyword must be added to the function declaration.

With Dynamic Parallelism on **sm_35**, several CUDA APIs can now be instantiated from the device. The following list defines single-step behavior when encountering these APIs:

- ▶ When encountering device side kernel launches (denoted by the `<<<>>>` launch syntax), the **step** and **next** commands will have the same behavior, and both will **step over** the launch call.
- ▶ When encountering `cudaDeviceSynchronize`, the launch synchronization routine, the **step** and **next** commands will have the same behavior, and both will **step over** the call. When stepping over the call, the **entire device** is resumed until the call has completed, at which point the device is suspended (without user intervention).
- ▶ When stepping a device grid launch to completion, focus will automatically switch back to the CPU. The `cuda kernel` focus switching command must be used to switch to another grid of interest (if one is still resident).



It is not possible to **step into** a device launch call (nor the routine launched by the call).

Chapter 7.

BREAKPOINTS

There are multiple ways to set a breakpoint on a CUDA application. Those methods are described below. The commands to set a breakpoint on the device code are the same as the commands used to set a breakpoint on the host code.

If the breakpoint is set on device code, the breakpoint will be marked pending until the ELF image of the kernel is loaded. At that point, the breakpoint will be resolved and its address will be updated.

When a breakpoint is set, it forces all resident GPU threads to stop at this location when it hits that corresponding PC.

When a breakpoint is hit by one thread, there is no guarantee that the other threads will hit the breakpoint at the same time. Therefore the same breakpoint may be hit several times, and the user must be careful with checking which thread(s) actually hit(s) the breakpoint.

7.1 Symbolic Breakpoints

To set a breakpoint at the entry of a function, use the **break** command followed by the name of the function or method:

```
(cuda-gdb) break my_function  
(cuda-gdb) break my_class::my_method
```

For templated functions and methods, the full signature must be given:

```
(cuda-gdb) break int my_templatized_function<int>(int)
```

The mangled name of the function can also be used. To find the mangled name of a function, you can use the following command:

```
(cuda-gdb) set demangle-style none  
(cuda-gdb) info function my_function_name  
(cuda-gdb) set demangle-style auto
```

7.2 Line Breakpoints

To set a breakpoint on a specific line number, use the following syntax:

```
(cuda-gdb) break my_file.cu:185
```

If the specified line corresponds to an instruction within templated code, multiple breakpoints will be created, one for each instance of the templated code.

7.3 Address Breakpoints

To set a breakpoint at a specific address, use the **break** command with the address as argument:

```
(cuda-gdb) break *0x1afe34d0
```

The address can be any address on the device or the host.

7.4 Kernel Entry Breakpoints

To break on the first instruction of every launched kernel, set the **break_on_launch** option to application:

```
(cuda-gdb) set cuda break_on_launch application
```

Possible options are:

application

kernel launched by the user application

system

any kernel launched by the driver, such as memset

all

any kernel, application and system

none

no kernel, application or system

Those automatic breakpoints are not displayed by the `info breakpoints` command and are managed separately from individual breakpoints. Turning off the option will not delete other individual breakpoints set to the same address and vice-versa.

Setting **break_on_launch** option to any value other than **none** would force [kernel_events](#) option to be set to **show**.

7.5 Conditional Breakpoints

To make the breakpoint conditional, use the optional `if` keyword or the `cond` command.

```
(cuda-gdb) break foo.cu:23 if threadIdx.x == 1 && i < 5
(cuda-gdb) cond 3 threadIdx.x == 1 && i < 5
```

Conditional expressions may refer any variable, including built-in variables such as **threadIdx** and **blockIdx**. Function calls are not allowed in conditional expressions.

Note that conditional breakpoints are always hit and evaluated, but the debugger reports the breakpoint as being hit only if the conditional statement is evaluated to TRUE. The process of hitting the breakpoint and evaluating the corresponding conditional statement is time-consuming. Therefore, running applications while using conditional breakpoints may slow down the debugging session. Moreover, if the conditional statement is always evaluated to FALSE, the debugger may appear to be hanging or stuck, although it is not the case. You can interrupt the application with **CTRL-C** to verify that progress is being made.

Conditional breakpoints can only be set on code from CUDA modules that are already loaded. Otherwise, CUDA-GDB will report an error that it is unable to find symbols in the current context. If unsure, first set an unconditional breakpoint at the desired location and add the conditional statement the first time the breakpoint is hit by using the **cond** command.

Chapter 8.

INSPECTING PROGRAM STATE

8.1 Memory and Variables

The GDB print command has been extended to decipher the location of any program variable and can be used to display the contents of any CUDA program variable including:

- ▶ data allocated via `cudaMalloc()`
- ▶ data that resides in various GPU memory regions, such as shared, local, and global memory
- ▶ special CUDA runtime variables, such as `threadIdx`

8.2 Variable Storage and Accessibility

Depending on the variable type and usage, variables can be stored either in registers or in `local`, `shared`, `const` or `global` memory. You can print the address of any variable to find out where it is stored and directly access the associated memory.

The example below shows how the variable `array`, which is of type `shared int *`, can be directly accessed in order to see what the stored values are in the array.

```
(cuda-gdb) print &array
$1 = (@shared int (*)[0]) 0x20
(cuda-gdb) print array[0]@4
$2 = {0, 128, 64, 192}
```

You can also access the shared memory indexed into the starting offset to see what the stored values are:

```
(cuda-gdb) print *(@shared int*)0x20
$3 = 0
(cuda-gdb) print *(@shared int*)0x24
$4 = 128
(cuda-gdb) print *(@shared int*)0x28
$5 = 64
```

The example below shows how to access the starting address of the input parameter to the kernel.

```
(cuda-gdb) print &data
$6 = (const @global void * const @parameter *) 0x10
(cuda-gdb) print *(@global void * const @parameter *) 0x10
$7 = (@global void * const @parameter) 0x110000</pre>

```

8.3 Inspecting Textures



The debugger can always read/write the source variables when the PC is on the first assembly instruction of a source instruction. When doing assembly-level debugging, the value of source variables is not always accessible.

To inspect a texture, use the print command while de-referencing the texture recast to the type of the array it is bound to. For instance, if texture `tex` is bound to array `A` of type `float*`, use:

```
(cuda-gdb) print *(@texture float *)tex
```

All the array operators, such as `[]`, can be applied to `(@texture float *)tex`:

```
(cuda-gdb) print ((@texture float *)tex)[2]
(cuda-gdb) print ((@texture float *)tex)[2][4]
```

8.4 Info CUDA Commands

These are commands that display information about the GPU and the application's CUDA state. The available options are:

devices

information about all the devices

sms

information about all the SMs in the current device

warps

information about all the warps in the current SM

lanes

information about all the lanes in the current warp

kernels

information about all the active kernels

blocks

information about all the active blocks in the current kernel

threads

information about all the active threads in the current kernel

launch trace

information about the parent kernels of the kernel in focus

launch children

information about the kernels launched by the kernels in focus

contexts

information about all the contexts

A filter can be applied to every **info cuda** command. The filter restricts the scope of the command. A filter is composed of one or more restrictions. A restriction can be any of the following:

- ▶ **device** *n*
- ▶ **sm** *n*
- ▶ **warp** *n*
- ▶ **lane** *n*
- ▶ **kernel** *n*
- ▶ **grid** *n*
- ▶ **block** *x[,y]* or **block** (*x[,y]*)
- ▶ **thread** *x[,y[,z]]* or **thread** (*x[,y[,z]]*)
- ▶ **breakpoint** *all* and **breakpoint** *n*

where *n*, *x*, *y*, *z* are integers, or one of the following special keywords: **current**, **any**, and **all**. **current** indicates that the corresponding value in the current focus should be used. **any** and **all** indicate that any value is acceptable.



The **breakpoint all** and **breakpoint n** filter are only effective for the **info cuda threads** command.

8.4.1 info cuda devices

This command enumerates all the GPUs in the system sorted by device index. A ***** indicates the device currently in focus. This command supports filters. The default is **device all**. This command prints **No CUDA Devices** if no GPUs are found.

```
(cuda-gdb) info cuda devices
Dev/Description/SM Type/SMs Warps/SM Lanes/Warp Max Regs/Lane/Active SMs Mask
* 0  gt200      sm_13      24        32        32        128      0x00ffffff
```

8.4.2 info cuda sms

This command shows all the SMs for the device and the associated active warps on the SMs. This command supports filters and the default is **device current sm all**. A ***** indicates the SM is focus. The results are grouped per device.

```
(cuda-gdb) info cuda sms SM Active Warps Mask Device 0
* 0  0xffffffffffffffffffff
1  0xffffffffffffffffffff
2  0xffffffffffffffffffff
3  0xffffffffffffffffffff
4  0xffffffffffffffffffff
5  0xffffffffffffffffffff
6  0xffffffffffffffffffff
7  0xffffffffffffffffffff
8  0xffffffffffffffffffff
...
```

8.4.3 info cuda warps

This command takes you one level deeper and prints all the warps information for the SM in focus. This command supports filters and the default is **device current sm current warp all**. The command can be used to display which warp executes what block.

```
(cuda-gdb) info cuda warps
Wp /Active Lanes Mask/ Divergent Lanes Mask/Active Physical PC/Kernel/BlockIdx
Device 0 SM 0
* 0  0xffffffff 0x00000000 0x0000000000000001c 0 (0,0,0)
  1  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  2  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  3  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  4  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  5  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  6  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  7  0xffffffff 0x00000000 0x00000000000000000 0 (0,0,0)
  ...
```

8.4.4 info cuda lanes

This command displays all the lanes (threads) for the warp in focus. This command supports filters and the default is **device current sm current warp current lane all**. In the example below you can see that all the lanes are at the same physical PC. The command can be used to display which lane executes what thread.

```
(cuda-gdb) info cuda lanes
Ln State Physical PC ThreadIdx
Device 0 SM 0 Warp 0
* 0 active 0x0000000000000008c (0,0,0)
  1 active 0x0000000000000008c (1,0,0)
  2 active 0x0000000000000008c (2,0,0)
  3 active 0x0000000000000008c (3,0,0)
  4 active 0x0000000000000008c (4,0,0)
  5 active 0x0000000000000008c (5,0,0)
  6 active 0x0000000000000008c (6,0,0)
  7 active 0x0000000000000008c (7,0,0)
  8 active 0x0000000000000008c (8,0,0)
  9 active 0x0000000000000008c (9,0,0)
 10 active 0x0000000000000008c (10,0,0)
 11 active 0x0000000000000008c (11,0,0)
 12 active 0x0000000000000008c (12,0,0)
 13 active 0x0000000000000008c (13,0,0)
 14 active 0x0000000000000008c (14,0,0)
 15 active 0x0000000000000008c (15,0,0)
 16 active 0x0000000000000008c (16,0,0)
  ...
```

8.4.5 info cuda kernels

This command displays on all the active kernels on the GPU in focus. It prints the SM mask, kernel ID, and the grid ID for each kernel with the associated dimensions and arguments. The kernel ID is unique across all GPUs whereas the grid ID is unique per GPU. The **Parent** column shows the kernel ID of the parent grid. This command supports filters and the default is **kernel all**.

```
(cuda-gdb) info cuda kernels
Kernel Parent Dev Grid Status   SMs Mask   GridDim   BlockDim   Name Args
*      1      -   0     2 Active 0x00ffffff (240,1,1) (128,1,1) acos_main
parms=...
```

This command will also show grids that have been launched on the GPU with Dynamic Parallelism. Kernels with a negative grid ID have been launched from the GPU, while kernels with a positive grid ID have been launched from the CPU.



With the `cudaDeviceSynchronize` routine, it is possible to see grid launches disappear from the device and then resume later after all child launches have completed.

8.4.6 info cuda blocks

This command displays all the active or running blocks for the kernel in focus. The results are grouped per kernel. This command supports filters and the default is **kernel current block all**. The outputs are coalesced by default.

```
(cuda-gdb) info cuda blocks
BlockIdx  To BlockIdx  Count  State
Kernel 1
* (0,0,0)    (191,0,0)    192    running
```

Coalescing can be turned off as follows in which case more information on the Device and the SM get displayed:

```
(cuda-gdb) set cuda coalescing off
```

The following is the output of the same command when coalescing is turned off.

```
(cuda-gdb) info cuda blocks
BlockIdx  State   Dev SM
Kernel 1
* (0,0,0)  running  0   0
  (1,0,0)  running  0   3
  (2,0,0)  running  0   6
  (3,0,0)  running  0   9
  (4,0,0)  running  0  12
  (5,0,0)  running  0  15
  (6,0,0)  running  0  18
  (7,0,0)  running  0  21
  (8,0,0)  running  0   1
  ...
```

8.4.7 info cuda threads

This command displays the application's active CUDA blocks and threads with the total count of threads in those blocks. Also displayed are the virtual PC and the associated source file and the line number information. The results are grouped per kernel. The command supports filters with default being **kernel current block all thread all**. This command also supports **breakpoint all** and **breakpoint breakpoint_number** filter. The former displays the threads that hit all

CUDA breakpoints set by the user. The latter displays the threads that hit the CUDA breakpoint *breakpoint_number*. The outputs are coalesced by default as follows:

```
(cuda-gdb) info cuda threads
  BlockIdx ThreadIdx To BlockIdx ThreadIdx Count  Virtual PC      Filename  Line
Device 0 SM 0
* (0,0,0) (0,0,0)    (0,0,0) (31,0,0)    32  0x0000000000088f88c  acos.cu
  376
  (0,0,0) (32,0,0)  (191,0,0) (127,0,0) 24544 0x0000000000088f800  acos.cu  374
  ...
```

Coalescing can be turned off as follows in which case more information is displayed with the output.

```
(cuda-gdb) info cuda threads
  BlockIdx ThreadIdx Virtual PC      Dev SM Wp Ln  Filename  Line
Kernel 1
* (0,0,0)    (0,0,0)  0x0000000000088f88c  0  0  0  0  acos.cu  376
  (0,0,0)    (1,0,0)  0x0000000000088f88c  0  0  0  1  acos.cu  376
  (0,0,0)    (2,0,0)  0x0000000000088f88c  0  0  0  2  acos.cu  376
  (0,0,0)    (3,0,0)  0x0000000000088f88c  0  0  0  3  acos.cu  376
  (0,0,0)    (4,0,0)  0x0000000000088f88c  0  0  0  4  acos.cu  376
  (0,0,0)    (5,0,0)  0x0000000000088f88c  0  0  0  5  acos.cu  376
  (0,0,0)    (6,0,0)  0x0000000000088f88c  0  0  0  6  acos.cu  376
  (0,0,0)    (7,0,0)  0x0000000000088f88c  0  0  0  7  acos.cu  376
  (0,0,0)    (8,0,0)  0x0000000000088f88c  0  0  0  8  acos.cu  376
  (0,0,0)    (9,0,0)  0x0000000000088f88c  0  0  0  9  acos.cu  376
  ...
```



In coalesced form, threads must be contiguous in order to be coalesced. If some threads are not currently running on the hardware, they will create *holes* in the thread ranges. For instance, if a kernel consist of 2 blocks of 16 threads, and only the 8 lowest threads are active, then 2 coalesced ranges will be printed: one range for block 0 thread 0 to 7, and one range for block 1 thread 0 to 7. Because threads 8-15 in block 0 are not running, the 2 ranges cannot be coalesced.

8.4.8 info cuda launch trace

This command displays the kernel launch trace for the kernel in focus. The first element in the trace is the kernel in focus. The next element is the kernel that launched this kernel. The trace continues until there is no parent kernel. In that case, the kernel is CPU-launched.

For each kernel in the trace, the command prints the level of the kernel in the trace, the kernel ID, the device ID, the status, the filename and line number where the launch of the direct child took place, the kernel name, the kernel dimensions, and the kernel arguments.

```
(cuda-gdb) info cuda launch trace
Depth Kernel Device      Status Launch Site Kernel Name  GridDim  BlockDim
Args
  0      3      0      Active  bar.cu:79   kernel3  (32,1,1) (16,1,1) c=5
  1      2      0  Terminated  foo.cu:12   kernel2 (240,1,1) (128,1,1) b=3
  2      1      0      Active           cpu    kernel1 (240,1,1) (128,1,1) a=1
```

A kernel that has been launched but that is not running on the GPU will have a **Pending** status. A kernel currently running on the GPU will be marked as **Active**. A kernel waiting to become active again will be displayed as **Sleeping**. When a kernel has terminated, it is marked as **Terminated**. For the few cases, when the debugger cannot determine if a kernel is pending or terminated, the status is set to **Undetermined**.

This command supports filters and the default is **kernel all**.

8.4.9 info cuda launch children

This command displays the list of non-terminated kernels launched by the kernel in focus. For each kernel, the kernel ID, the device ID, the launch location in the parent kernel, the kernel name, the kernel dimensions, and the kernel parameters are displayed.

```
(cuda-gdb) info cuda launch children
Kernel Device Launch Site Kernel Name GridDim BlockDim Args
      3      0   foo.cu:12   kernel5  (1,1,1)  (1,1,1) a=3
     18      0   bar.cu:72   kernel4  (1,1,1) (32,1,1) b=5
```

This command supports filters and the default is **kernel all**.

8.4.10 info cuda contexts

This command enumerates all the CUDA contexts running on all GPUs. A ***** indicates the context currently in focus. This command shows whether a context is currently active on a device or not.

```
(cuda-gdb) info cuda contexts
Context Dev State
0x080b9518 0 inactive
* 0x08067948 0 active
```

8.5 Disassembly

The device SASS code can be disassembled using the standard GDB disassembly instructions such as **x/i** and **display/i**.

```
(cuda-gdb) x/4 $pc
=> 0x7a5cf0 <_Z9foo10Params(Params)+752>: IMUL R2, R0, R3
    0x7a5cf8 <_Z9foo10Params(Params)+760>: MOV R3, R4
    0x7a5d00 <_Z9foo10Params(Params)+768>: IMUL R0, R0, R3
    0x7a5d08 <_Z9foo10Params(Params)+776>: IADD R18, R0, R3
```



For disassembly instruction to work properly, **cuobjdump** must be installed and present in your **\$PATH**.

Chapter 9.

CONTEXT AND KERNEL EVENTS

Within CUDA-GDB, *kernel* refers to your device code that executes on the GPU, while *context* refers to the virtual address space on the GPU for your kernel.

You can turn ON or OFF the display of CUDA context and kernel events to review the flow of the active contexts and kernels.

9.1 Display CUDA context events

- ▶ `(cuda-gdb) set cuda context_events 1`

Display CUDA context events.

- ▶ `(cuda-gdb) set cuda context_events 0`

Do not display CUDA context events.

9.2 Display CUDA kernel events

By default **kernel_events** option is set to show all kernel events synchronously.

- ▶ `(cuda-gdb) set cuda kernel_events show_sync`

Display CUDA kernel events synchronously.

- ▶ `(cuda-gdb) set cuda kernel_events show_async`

Display CUDA kernel events asynchronously.

Asynchronous kernel events are less accurate and reported only during next breakpoint, but if enabled results in debugged program execution speedup for applications launching lots of kernels.

If **break_on_all** option is set to any value other than none kernel events would be delivered synchronously.

- ▶ `(cuda-gdb) set cuda kernel_events hide`

Do not display CUDA kernel events.

9.3 Examples of displayed events

The following are examples of context events displayed:

```
[Context Create of context 0xad2fe60 on Device 0]
```

```
[Context Pop of context 0xad2fe60 on Device 0]
```

```
[Context Destroy of context 0xad2fe60 on Device 0]
```

The following are examples of kernel events displayed:

```
[Launch of CUDA Kernel 1 (kernel3) on Device 0]
```

```
[Termination of CUDA Kernel 1 (kernel3) on Device 0]
```



The kernel termination event is only displayed when a kernel is launched asynchronously, or when the debugger can safely assume that the kernel has terminated.

Chapter 10.

CHECKING MEMORY ERRORS

The CUDA memcheck feature detects global memory violations and mis-aligned global memory accesses. This feature is off by default and can be enabled using the following variable in CUDA-GDB before the application is run.

```
(cuda-gdb) set cuda memcheck on
```

Once CUDA memcheck is enabled, any detection of global memory violations and mis-aligned global memory accesses will be reported.

When CUDA memcheck is enabled, all the kernel launches are made blocking, as if the environment variable **CUDA_LAUNCH_BLOCKING** was set to 1. The host thread launching a kernel will therefore wait until the kernel has completed before proceeding. This may change the behavior of your application.

You can also run the CUDA memory checker as a standalone tool named CUDA-MEMCHECK. This tool is also part of the toolkit. Please read the related documentation for more information.

By default, CUDA-GDB will report any memory error. See [Increasing the Precision of Memory Errors With Autostep](#) for a list of the memory errors. To increase the number of memory errors being reported and to increase the precision of the memory errors, CUDA memcheck must be turned on.

10.1 Increasing the Precision of Memory Errors With Autostep

Autostep is a command to increase the precision of CUDA exceptions to the exact lane and instruction, when they would not have been otherwise.

Under normal execution, an exception may be reported several instructions after the exception occurred, or the exact thread where an exception occurred may not be known unless the exception is a lane error. However, the precise origin of the exception can be determined if the program is being single-stepped when the exception occurs. Single-stepping manually is a slow and tedious process; stepping takes much longer than normal execution and the user has to single-step each warp individually.

Autostep aides the user by allowing them to specify sections of code where they suspect an exception could occur, and these sections are automatically and transparently single-stepped the program is running. The rest of the program is executed normally to minimize the slow-down caused by single-stepping. The precise origin of an exception will be reported if the exception occurs within these sections. Thus the exact instruction and thread where an exception occurred can be found quickly and with much less effort by using autostep.

10.1.1 Usage

```
autostep [LOCATION]
autostep [LOCATION] for LENGTH [lines|instructions]
```

- ▶ **LOCATION** may be anything that you use to specify the location of a breakpoint, such as a line number, function name, or an instruction address preceded by an asterisk. If no **LOCATION** is specified, then the current instruction address is used.
- ▶ **LENGTH** specifies the size of the autostep window in number of lines or instructions (*lines* and *instructions* can be shortened, e.g., *l* or *i*). If the length type is not specified, then *lines* is the default. If the **for** clause is omitted, then the default is 1 line.
- ▶ **astep** can be used as an alias for the **autostep** command.
- ▶ Calls to functions made during an autostep will be stepped over.
- ▶ In case of divergence, the length of the autostep window is determined by the number of lines or instructions the first active lane in each warp executes.

Divergent lanes are also single stepped, but the instructions they execute do not count towards the length of the autostep window.

- ▶ If a breakpoint occurs while inside an autostep window, the warp where the breakpoint was hit will not continue autostepping when the program is resumed. However, other warps may continue autostepping.
- ▶ Overlapping autosteps are not supported.

If an autostep is encountered while another autostep is being executed, then the second autostep is ignored.

If an autostep is set before the location of a memory error and no memory error is hit, then it is possible that the chosen window is too small. This may be caused by the presence of function calls between the address of the autostep location and the instruction that triggers the memory error. In that situation, either increase the size of the window to make sure that the faulty instruction is included, or move to the autostep location to an instruction that will be executed closer in time to the faulty instruction.



Autostep requires Fermi GPUs or above.

10.1.2 Related Commands

Autosteps and breakpoints share the same numbering so most commands that work with breakpoints will also work with autosteps.

10.1.2.1 info autosteps

Shows all breakpoints and autosteps. Similar to **info breakpoints**.

```
(cuda-gdb) info autosteps
Num  Type      Disp Enb Address          What
1    autostep keep y  0x0000000000401234 in merge at sort.cu:30 for 49
    instructions
3    autostep keep y  0x0000000000489913 in bubble at sort.cu:94 for 11 lines
```

10.1.2.2 disable autosteps n

Disables an autostep. Equivalent to **disable breakpoints n**.

10.1.2.3 delete autosteps n

Deletes an autostep. Equivalent to **delete breakpoints n**.

10.1.2.4 ignore n i

Do not single-step the next *i* times the debugger enters the window for autostep *n*. This command already exists for breakpoints.

10.2 GPU Error Reporting

With improved GPU error reporting in CUDA-GDB, application bugs are now easier to identify and easy to fix. The following table shows the new errors that are reported on GPUs with compute capability **sm_20** and higher.



Continuing the execution of your application after these errors are found can lead to application termination or indeterminate results.

Table 1 CUDA Exception Codes

Exception Code	Precision of the Error	Scope of the Error	Description
CUDA_EXCEPTION_0 : "Device Unknown Exception"	Not precise	Global error on the GPU	This is a global GPU error caused by the application which does not match any of the listed error codes below. This should be a rare occurrence.

Exception Code	Precision of the Error	Scope of the Error	Description
			Potentially, this may be due to Device Hardware Stack overflows or a kernel generating an exception very close to its termination.
CUDA_EXCEPTION_1 : "Lane Illegal Address"	Precise (Requires memcheck on)	Per lane/ thread error	This occurs when a thread accesses an illegal(out of bounds) global address.
CUDA_EXCEPTION_2 : "Lane User Stack Overflow"	Precise	Per lane/ thread error	This occurs when a thread exceeds its stack memory limit.
CUDA_EXCEPTION_3 : "Device Hardware Stack Overflow"	Not precise	Global error on the GPU	This occurs when the application triggers a global hardware stack overflow. The main cause of this error is large amounts of divergence in the presence of function calls.
CUDA_EXCEPTION_4 : "Warp Illegal Instruction"	Not precise	Warp error	This occurs when any thread within a warp has executed an illegal instruction.
CUDA_EXCEPTION_5 : "Warp Out-of-range Address"	Not precise	Warp error	This occurs when any thread within a warp accesses an address that is outside the valid range of local or shared memory regions.
CUDA_EXCEPTION_6 : "Warp Misaligned Address"	Not precise	Warp error	This occurs when any thread within a warp accesses an address in the local or shared memory segments that is not correctly aligned.
CUDA_EXCEPTION_7 : "Warp Invalid Address Space"	Not precise	Warp error	This occurs when any thread within a warp executes an instruction that accesses a memory space not permitted for that instruction.
CUDA_EXCEPTION_8 : "Warp Invalid PC"	Not precise	Warp error	This occurs when any thread within a warp advances its PC beyond the 40-bit address space.

Exception Code	Precision of the Error	Scope of the Error	Description
<code>CUDA_EXCEPTION_9 : "Warp Hardware Stack Overflow"</code>	Not precise	Warp error	This occurs when any thread in a warp triggers a hardware stack overflow. This should be a rare occurrence.
<code>CUDA_EXCEPTION_10 : "Device Illegal Address"</code>	Not precise	Global error	This occurs when a thread accesses an illegal(out of bounds) global address. For increased precision, use the cuda memcheck feature.
<code>CUDA_EXCEPTION_11 : "Lane Misaligned Address"</code>	Precise (Requires memcheck on)	Per lane/ thread error	This occurs when a thread accesses a global address that is not correctly aligned.
<code>CUDA_EXCEPTION_12 : "Warp Assert"</code>	Precise	Per warp	This occurs when any thread in the warp hits a device side assertion.

Chapter 11.

CHECKING API ERRORS

CUDA-GDB can automatically check the return code of any driver API or runtime API call. If the return code indicates an error, the debugger will stop or warn the user.

The behavior is controlled with the `set cuda api_failures` option. Three modes are supported:

- ▶ **hide** will not report any error of any kind
- ▶ **ignore** will emit a warning but continue the execution of the application (default)
- ▶ **stop** will emit an error and stop the application



The success return code and other non-error return codes are ignored. For the driver API, those are: `CUDA_SUCCESS` and `CUDA_ERROR_NOT_READY`. For the runtime API, they are `cudaSuccess` and `cudaErrorNotReady`.

Chapter 12.

WALK-THROUGH EXAMPLES

The chapter contains two CUDA-GDB walk-through examples:

- ▶ Example 1: bitreverse
- ▶ Example 2: autostep
- ▶ Example 3: Debugging an MPI CUDA Application

12.1 Example 1: bitreverse

This section presents a walk-through of CUDA-GDB by debugging a sample application—called **bitreverse**—that performs a simple 8 bit reversal on a data set.

Source Code

```
1  #include <stdio.h>
2  #include <stdlib.h>
3
4  // Simple 8-bit bit reversal Compute test
5
6  #define N 256
7
8  __global__ void bitreverse(void *data) {
9      unsigned int *idata = (unsigned int*)data;
10     extern __shared__ int array[];
11
12     array[threadIdx.x] = idata[threadIdx.x];
13
14     array[threadIdx.x] = ((0xf0f0f0f0 & array[threadIdx.x]) >> 4) |
15                         ((0x0f0f0f0f & array[threadIdx.x]) << 4);
16     array[threadIdx.x] = ((0xcccccccc & array[threadIdx.x]) >> 2) |
17                         ((0x33333333 & array[threadIdx.x]) << 2);
18     array[threadIdx.x] = ((0xaaaaaaaa & array[threadIdx.x]) >> 1) |
19                         ((0x55555555 & array[threadIdx.x]) << 1);
20
21     idata[threadIdx.x] = array[threadIdx.x];
22 }
23
24 int main(void) {
25     void *d = NULL; int i;
26     unsigned int idata[N], odata[N];
27
28     for (i = 0; i < N; i++)
29         idata[i] = (unsigned int)i;
```

```

30
31     cudaMalloc((void**)&d, sizeof(int)*N);
32     cudaMemcpy(d, idata, sizeof(int)*N,
33               cudaMemcpyHostToDevice);
34
35     bitreverse<<<1, N, N*sizeof(int)>>>(d);
36
37     cudaMemcpy(odata, d, sizeof(int)*N,
38               cudaMemcpyDeviceToHost);
39
40     for (i = 0; i < N; i++)
41         printf('%u -> %u\n', idata[i], odata[i]);
42
43     cudaFree((void*)d);
44     return 0;
45 }

```

12.1.1 Walking through the Code

1. Begin by compiling the **bitreverse.cu** CUDA application for debugging by entering the following command at a shell prompt:

```
$ nvcc -g -G bitreverse.cu -o bitreverse
```

This command assumes that the source file name is **bitreverse.cu** and that no additional compiler flags are required for compilation. See also [Debug Compilation](#)

2. Start the CUDA debugger by entering the following command at a shell prompt:

```
$ cuda-gdb bitreverse
```

3. Set breakpoints. Set both the host (**main**) and GPU (**bitreverse**) breakpoints here. Also, set a breakpoint at a particular line in the device function (**bitreverse.cu:18**).

```

(cuda-gdb) break main
Breakpoint 1 at 0x18e1: file bitreverse.cu, line 25.
(cuda-gdb) break bitreverse
Breakpoint 2 at 0x18a1: file bitreverse.cu, line 8.
(cuda-gdb) break 21
Breakpoint 3 at 0x18ac: file bitreverse.cu, line 21.

```

4. Run the CUDA application, and it executes until it reaches the first breakpoint (**main**) set in 3.

```

(cuda-gdb) run
Starting program: /Users/CUDA_User1/docs/bitreverse
Reading symbols for shared libraries
..++..... done

Breakpoint 1, main () at bitreverse.cu:25
25 void *d = NULL; int i;

```

5. At this point, commands can be entered to advance execution or to print the program state. For this walkthrough, let's continue until the device kernel is launched.

```

(cuda-gdb) continue
Continuing.
Reading symbols for shared libraries .. done
Reading symbols for shared libraries .. done
[Context Create of context 0x80f200 on Device 0]
[Launch of CUDA Kernel 0 (bitreverse<<<(1,1,1),(256,1,1)>>>) on Device 0]
Breakpoint 3 at 0x8667b8: file bitreverse.cu, line 21.

```

```
[Switching focus to CUDA kernel 0, grid 1, block (0,0,0), thread (0,0,0),
device 0, sm 0, warp 0, lane 0]
```

```
Breakpoint 2, bitreverse<<<(1,1,1),(256,1,1)>>> (data=0x110000) at
bitreverse.cu:9
9 unsigned int *idata = (unsigned int*)data;
```

CUDA-GDB has detected that a CUDA device kernel has been reached. The debugger prints the current CUDA thread of focus.

6. Verify the CUDA thread of focus with the **info cuda threads** command and switch between host thread and the CUDA threads:

```
(cuda-gdb) info cuda threads
BlockIdx ThreadIdx To BlockIdx ThreadIdx Count Virtual PC
Filename Line
Kernel 0
* (0,0,0) (0,0,0) (0,0,0) (255,0,0) 256 0x0000000000866400
bitreverse.cu 9
(cuda-gdb) thread
[Current thread is 1 (process 16738)]
(cuda-gdb) thread 1
[Switching to thread 1 (process 16738)]
#0 0x000019d5 in main () at bitreverse.cu:34
34 bitreverse<<<1, N, N*sizeof(int)>>>(d);
(cuda-gdb) backtrace
#0 0x000019d5 in main () at bitreverse.cu:34
(cuda-gdb) info cuda kernels
Kernel Dev Grid SMS Mask GridDim BlockDim Name Args
0 0 1 0x00000001 (1,1,1) (256,1,1) bitreverse data=0x110000
(cuda-gdb) cuda kernel 0
[Switching focus to CUDA kernel 0, grid 1, block (0,0,0), thread (0,0,0),
device 0, sm 0, warp 0, lane 0]
9 unsigned int *idata = (unsigned int*)data;
(cuda-gdb) backtrace
#0 bitreverse<<<(1,1,1),(256,1,1)>>> (data=0x110000) at bitreverse.cu:9
```

7. Corroborate this information by printing the block and thread indexes:

```
(cuda-gdb) print blockIdx
$1 = {x = 0, y = 0}
(cuda-gdb) print threadIdx
$2 = {x = 0, y = 0, z = 0}
```

8. The grid and block dimensions can also be printed:

```
(cuda-gdb) print gridDim
$3 = {x = 1, y = 1}
(cuda-gdb) print blockDim
$4 = {x = 256, y = 1, z = 1}
```

9. Advance kernel execution and verify some data:

```
(cuda-gdb) next
12 array[threadIdx.x] = idata[threadIdx.x];
(cuda-gdb) next
14 array[threadIdx.x] = ((0xf0f0f0f0 & array[threadIdx.x]) >> 4) |
(cuda-gdb) next
16 array[threadIdx.x] = ((0xcccccccc & array[threadIdx.x]) >> 2) |
(cuda-gdb) next
18 array[threadIdx.x] = ((0aaaaaaaa & array[threadIdx.x]) >> 1) |
(cuda-gdb) next
Breakpoint 3, bitreverse <<<(1,1),(256,1,1)>>> (data=0x100000) at
bitreverse.cu:21
21 idata[threadIdx.x] = array[threadIdx.x];
```

```
(cuda-gdb) print array[0]@12
$7 = {0, 128, 64, 192, 32, 160, 96, 224, 16, 144, 80, 208}
(cuda-gdb) print/x array[0]@12
$8 = {0x0, 0x80, 0x40, 0xc0, 0x20, 0xa0, 0x60, 0xe0, 0x10, 0x90, 0x50, 0xd0}

(cuda-gdb) print &data
$9 = (@global void * @parameter *) 0x10
(cuda-gdb) print *(@global void * @parameter *) 0x10
$10 = (@global void * @parameter) 0x100000
```

The resulting output depends on the current content of the memory location.

10 Since thread (0,0,0) reverses the value of 0, switch to a different thread to show more interesting data:

```
(cuda-gdb) cuda thread 170
[Switching focus to CUDA kernel 0, grid 1, block (0,0,0), thread
(170,0,0), device 0, sm 0, warp 5, lane 10]
```

11 Delete the breakpoints and continue the program to completion:

```
(cuda-gdb) delete breakpoints
Delete all breakpoints? (y or n) y
(cuda-gdb) continue
Continuing.

Program exited normally.
(cuda-gdb)
```

12.2 Example 2: autostep

This section shows how to use the autostep command and demonstrates how it helps increase the precision of memory error reporting.

Source Code

```
1 #define NUM_BLOCKS 8
2 #define THREADS_PER_BLOCK 64
3
4 __global__ void example(int **data) {
5     int value1, value2, value3, value4, value5;
6     int idx1, idx2, idx3;
7
8     idx1 = blockIdx.x * blockDim.x;
9     idx2 = threadIdx.x;
10    idx3 = idx1 + idx2;
11    value1 = *(data[idx1]);
12    value2 = *(data[idx2]);
13    value3 = value1 + value2;
14    value4 = value1 * value2;
15    value5 = value3 + value4;
16    *(data[idx3]) = value5;
17    *(data[idx1]) = value3;
18    *(data[idx2]) = value4;
19    idx1 = idx2 = idx3 = 0;
20 }
21
22 int main(int argc, char *argv[]) {
23     int *host_data[NUM_BLOCKS * THREADS_PER_BLOCK];
24     int **dev_data;
25     const int zero = 0;
26 }
```

```

27  /* Allocate an integer for each thread in each block */
28  for (int block = 0; block << NUM_BLOCKS; block++) {
29      for (int thread = 0; thread << THREADS_PER_BLOCK; thread++) {
30          int idx = thread + block * THREADS_PER_BLOCK;
31          cudaMalloc(&host_data[idx], sizeof(int));
32          cudaMemcpy(host_data[idx], &zero, sizeof(int),
33                    cudaMemcpyHostToDevice);
34      }
35  }
36
37  /* This inserts an error into block 3, thread 39*/
38  host_data[3*THREADS_PER_BLOCK + 39] = NULL;
39
40  /* Copy the array of pointers to the device */
41  cudaMalloc((void**)&dev_data, sizeof(host_data));
42  cudaMemcpy(dev_data, host_data, sizeof(host_data), cudaMemcpyHostToDevice);
43
44  /* Execute example */
45  example <<< <<< NUM_BLOCKS, THREADS_PER_BLOCK >>> (dev_data);
46  cudaThreadSynchronize();
47 }

```

In this small example, we have an array of pointers to integers, and we want to do some operations on the integers. Suppose, however, that one of the pointers is NULL as shown in line 38. This will cause **CUDA_EXCEPTION_10 "Device Illegal Address"** to be thrown when we try to access the integer that corresponds with block 3, thread 39. This exception should occur at line 16 when we try to write to that value.

12.2.1 Debugging with Autosteps

1. Compile the example and start CUDA-GDB as normal. We begin by running the program:

```

(cuda-gdb) run
Starting program: /home/jitud/cudagdb_test/autostep_ex/example
[Thread debugging using libthread_db enabled] [New Thread 0x7ffff5688700 (LWP
9083)]
[Context Create of context 0x617270 on Device 0]
[Launch of CUDA Kernel 0 (example<<<(8,1,1),(64,1,1)>>>) on Device 0]

Program received signal CUDA_EXCEPTION_10, Device Illegal Address.
[Switching focus to CUDA kernel 0, grid 1, block (1,0,0), thread (0,0,0),
device 0, sm 1, warp 0, lane 0]
0x000000000796f60 in example (data=0x200300000) at example.cu:17
17      *(data[idx1]) = value3;

```

As expected, we received a **CUDA_EXCEPTION_10**. However, the reported thread is block 1, thread 0 and the line is 17. Since **CUDA_EXCEPTION_10** is a Global error, there is no thread information that is reported, so we would manually have to inspect all 512 threads.

2. Set **autosteps**. To get more accurate information, we reason that since **CUDA_EXCEPTION_10** is a memory access error, it must occur on code that accesses memory. This happens on lines 11, 12, 16, 17, and 18, so we set two autostep windows for those areas:

```

(cuda-gdb) autostep 11 for 2 lines
Breakpoint 1 at 0x796d18: file example.cu, line 11.
Created autostep of length 2 lines
(cuda-gdb) autostep 16 for 3 lines

```

```
Breakpoint 2 at 0x796e90: file example.cu, line 16.
Created autostep of length 3 lines
```

3. Finally, we run the program again with these autosteps:

```
(cuda-gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
[Termination of CUDA Kernel 0 (example<<<(8,1,1),(64,1,1)>>>) on Device 0]
Starting program: /home/jitud/cudagdb_test/autostep_ex/example
[Thread debugging using libthread_db enabled]
[New Thread 0x7ffff5688700 (LWP 9089)]
[Context Create of context 0x617270 on Device 0]
[Launch of CUDA Kernel 1 (example<<<(8,1,1),(64,1,1)>>>) on Device 0]
[Switching focus to CUDA kernel 1, grid 1, block (0,0,0), thread (0,0,0),
device 0, sm 0, warp 0, lane 0]

Program received signal CUDA_EXCEPTION_10, Device Illegal Address.
[Current focus set to CUDA kernel 1, grid 1, block (3,0,0), thread
(32,0,0), device 0, sm 1, warp 3, lane 0]
Autostep precisely caught exception at example.cu:16 (0x796e90)
```

This time we correctly caught the exception at line 16. Even though **CUDA_EXCEPTION_10** is a global error, we have now narrowed it down to a warp error, so we now know that the thread that threw the exception must have been in the same warp as block 3, thread 32.

In this example, we have narrowed down the scope of the error from 512 threads down to 32 threads just by setting two **autosteps** and re-running the program.

12.3 Example 3: Debugging an MPI CUDA Application

For doing large MPI CUDA application debugging, NVIDIA recommends using parallel debuggers supplied by our partners Allinea and Totalview. Both make excellent parallel debuggers with extended support for CUDA. However, for debugging smaller applications, or for debugging just a few processes in a large application, CUDA-GDB can easily be used.

If the cluster nodes have xterm support, then it is quite easy to use CUDA-GDB. Just launch CUDA-GDB in the same way you would have launched gdb.

```
$ mpirun -np 4 -host nv1,nv2 xterm -e cuda-gdb a.out
```

You may have to export the DISPLAY variable to make sure that the xterm finds its way back to your display. For example, with Open MPI you would do something like this.

```
$ mpirun -np 4 -host nv1,nv2 -x DISPLAY=host.nvidia.com:0 xterm -e cuda-gdb
a.out
```

Different MPI implementations have different ways of exporting environment variables to the cluster nodes so check your documentation.

In the case where you cannot get xterm support, you can insert a spin loop inside your program. This works in just the same way as when using gdb on a host only program. Somewhere near the start of your program, add a code snippet like the following.

```
{
    int i = 0;
    char host[256];
    printf("PID %d on node %s is ready for attach\n",
           getpid(), host);
    fflush(stdout);
    while (0 == i) {
        sleep(5);
    }
}
```

Then recompile and run the program. After it starts, ssh to the nodes of interest and attach to the process. Set the variable `i` to 1 to break out of the loop.

```
$ mpirun -np 2 -host nv1,nv2 a.out
PID 20060 on node nv1 is ready for attach
PID 5488 on node nv2 is ready for attach
```

```
[nv1]$ cuda-gdb --pid 5488
```

```
[nv2]$ cuda-gdb --pid 20060
```

For larger applications in the case where you may just want to attach to a few of the processes, you can conditionalize the spin loop based on the rank. Most MPIs set an environment variable that is the rank of the process. For Open MPI it is `OMPI_COMM_WORLD_RANK` and for MVAPICH it is `MV2_COMM_WORLD_RANK`. Assuming you want to attach to rank 42, you could add a spin loop like this.

```
{
    char *stoprank;
    stoprank = getenv("OMPI_COMM_WORLD_RANK");
    if (42 == atoi(stoprank)) {
        int i = 0;
        char hostname[256];
        printf("PID %d on %s ready for attach\n",
               getpid(), hostname);
        fflush(stdout);
        while (0 == i) {
            sleep(5);
        }
    }
}
```

Note that there is currently a limitation of running only one CUDA-GDB process per node. The workaround described in [Multiple Debuggers](#) does not work with MPI applications. If `CUDA_VISIBLE_DEVICES` is set, it may cause problems with the GPU selection logic in the MPI application. It may also prevent CUDA IPC working between GPUs on a node. Therefore, for the current release, use only one CUDA-GDB per node with an MPI application.

Appendix A.

SUPPORTED PLATFORMS

The general platform and GPU requirements for running NVIDIA CUDA-GDB are described in this section.

A.1 Host Platform Requirements

Mac OS

CUDA-GDB is supported on both 32-bit and 64-bit editions of the following Mac OS versions:

- ▶ Mac OS X 10.7
- ▶ Mac OS X 10.8

Linux

CUDA-GDB is supported on both 32-bit and 64-bit editions of the following Linux distributions:

- ▶ Red Hat Enterprise Linux 5.5+ (64-bit only)
- ▶ Red Hat Enterprise Linux 6.x
- ▶ Ubuntu 12.04 and 12.10
- ▶ Fedora 18
- ▶ OpenSuse 12.2
- ▶ Suse Linux Enterprise Server 11.1 and 11 SP2

GPU Requirements

Debugging is supported on all CUDA-capable GPUs with a compute capability of 1.1 or later. *Compute capability* is a device attribute that a CUDA application can query about; for more information, see the latest *NVIDIA CUDA Programming Guide* on the NVIDIA CUDA Zone Web site: <http://developer.nvidia.com/object/gpucomputing.html>.

These GPUs have a compute capability of 1.0 and are *not supported*:

- ▶ GeForce 8800 GTS
- ▶ GeForce 8800 GTX
- ▶ GeForce 8800 Ultra
- ▶ Quadro Plex 1000 Model IV
- ▶ Quadro Plex 2100 Model S4
- ▶ Quadro FX 4600
- ▶ Quadro FX 5600
- ▶ Tesla C870
- ▶ Tesla D870
- ▶ Tesla S870

Appendix B. KNOWN ISSUES

The following are known issues with the current release.

- ▶ Setting the `cuda memcheck` option ON will make all the launches blocking.
- ▶ Device memory allocated via `cudaMalloc()` is not visible outside of the kernel function.
- ▶ On GPUs with `sm_type` lower than `sm_20` it is not possible to step over a subroutine in the device code.
- ▶ Requesting to read or write GPU memory may be unsuccessful if the size is larger than 100MB on Tesla GPUs and larger than 32MB on Fermi GPUs.
- ▶ On GPUs with `sm_20`, if you are debugging code in device functions that get called by multiple kernels, then setting a breakpoint in the device function will insert the breakpoint in only one of the kernels.
- ▶ In a multi-GPU debugging environment on Mac OS X with Aqua running, you may experience some visible delay while single-stepping the application.
- ▶ Setting a breakpoint on a line within a `__device__` or `__global__` function before its module is loaded may result in the breakpoint being temporarily set on the first line of a function below in the source code. As soon as the module for the targeted function is loaded, the breakpoint will be reset properly. In the meantime, the breakpoint may be hit, depending on the application. In those situations, the breakpoint can be safely ignored, and the application can be resumed.
- ▶ The *scheduler-locking* option cannot be set to *on*.
- ▶ Stepping again after stepping out of a kernel results in undetermined behavior. It is recommended to use the 'continue' command instead.
- ▶ OpenGL applications may require to launch X in non-interactive mode. See [CUDA/OpenGL Interop Applications on Linux](#) for details.

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication of otherwise under any patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all other information previously supplied. NVIDIA Corporation products are not authorized as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA and the NVIDIA logo are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2007-2012 NVIDIA Corporation. All rights reserved.